

HDD DRILL

TRACTO GRUNDODRILL 5X

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
50 kN	**1,627 Nm**

ENGINE POWER
41 kW

Technical specifications

PERFORMANCE

Pullback force	**50 kN**	Thrust force	**50 kN**
Maximum spindle torque	**1,627 Nm**	Maximum spindle speed	**200 rpm**
Minimum entry angle	**11 °**	Maximum entry angle	**17 °**

DRILL RODS AND BORE

Drill pipe length	**1.525 m**	Onboard rod capacity	**61 m**
Minimum bend radius	**29.3 m**		

DRILLING FLUID SYSTEM

Mud pump flow rate	**37.8 l/min**	Mud pump pressure	**69 bar**

POWERTRAIN AND ENGINE

Powertrain type	**diesel**	Engine manufacturer	**Kohler**
Engine power	**41 kW**	Emission standard	**Stage V**
Fuel tank capacity	**72 l**		

DIMENSIONS AND WEIGHT

Weight	**3,266 kg**	Transport length	**3,830 mm**
Transport width	**915 mm**	Transport height	**1,950 mm**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.