

HDD DRILL

TRACTO GRUNDODRILL 15XP

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
147 kN	**4,500 Nm**

ENGINE POWER
123 kW

Technical specifications

PERFORMANCE

Pullback force	**147 kN**	Thrust force	**147 kN**
Maximum spindle torque	**4,500 Nm**	Maximum spindle speed	**185 rpm**
Maximum carriage feed speed	**48 m/min**	Minimum entry angle	**0 °**
Maximum entry angle	**20 °**		

DRILL RODS AND BORE

Drill pipe length	**3 m**	Drill pipe diameter	**62 mm**
Onboard rod capacity	**210 m**	Rod count	**70 szt.**
Minimum bend radius	**42 m**	Pilot bore diameter	**100 mm**
Indicative maximum bore length	**350 m**		

DRILLING FLUID SYSTEM

Mud pump flow rate	**200 l/min**	Mud pump pressure	**90 bar**

POWERTRAIN AND ENGINE

Powertrain type	**diesel**	Engine manufacturer	**Cummins**
Engine power	**123 kW**	Emission standard	**Stage V**
Fuel tank capacity	**120 l**		

DIMENSIONS AND WEIGHT

Weight	**10,460 kg**	Transport length	**6,500 mm**
Transport width	**1,850 mm**	Transport height	**2,400 mm**

EQUIPMENT AND CAPABILITIES

Maximum backreaming diameter	**500 mm**		

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.