

HDD DRILL

TRACTO GRUNDODRILL 18ACS

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
180 kN	**7,500 Nm**

ENGINE POWER
123 kW

Technical specifications

PERFORMANCE			
Pullback force	**180 kN**	Thrust force	**180 kN**
Maximum spindle torque	**7,500 Nm**	Inner spindle torque	**2,500 Nm**
Maximum spindle speed	**200 rpm**	Maximum carriage feed speed	**36 m/min**
Minimum entry angle	**0 °**	Maximum entry angle	**30 °**

DRILL RODS AND BORE			
Drill pipe length	**3 m**	Indicative maximum bore length	**400 m**

DRILLING FLUID SYSTEM			
Mud pump flow rate	**320 l/min**	Mud pump pressure	**90 bar**

POWERTRAIN AND ENGINE

Powertrain type	**diesel**	Engine manufacturer	**Cummins**
Engine power	**123 kW**	Emission standard	**Stage V**
Fuel tank capacity	**180 l**		

DIMENSIONS AND WEIGHT

Weight	**16,190 kg**	Transport length	**6,700 mm**
Transport width	**2,350 mm**	Transport height	**2,620 mm**

EQUIPMENT AND CAPABILITIES

Dual-rod drilling system	**Yes**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.