

HDD DRILL

TRACTO GRUNDODRILL 28Nplus

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
280 kN	**11,000 Nm**

ENGINE POWER
224 kW

Technical specifications

PERFORMANCE			
Pullback force	**280 kN**	Thrust force	**280 kN**
Maximum spindle torque	**11,000 Nm**	Maximum spindle speed	**180 rpm**
Minimum entry angle	**0 °**	Maximum entry angle	**30 °**

DRILL RODS AND BORE			
Drill pipe length	**3 m**	Drill pipe diameter	**82 mm**
Onboard rod capacity	**288 m**	Indicative maximum bore length	**500 m**

DRILLING FLUID SYSTEM			
Mud pump flow rate	**650 l/min**	Mud pump pressure	**90 bar**

POWERTRAIN AND ENGINE			
Powertrain type	**diesel**	Engine power	**224 kW**

DIMENSIONS AND WEIGHT

Weight	**19,200 kg**	Transport length	**7,600 mm**
Transport width	**2,530 mm**	Transport height	**2,900 mm**

EQUIPMENT AND CAPABILITIES

Automatic rod exchange	**Yes**	Enclosed operator cabin	**Yes**
Maximum backreaming diameter	**900 mm**		

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.