

HDD DRILL

TRACTO GRUNDODRILL ACS130

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
130 kN	**4,500 Nm**

ENGINE POWER
115 kW

Technical specifications

PERFORMANCE

Pullback force	**130 kN**	Thrust force	**130 kN**
Maximum spindle torque	**4,500 Nm**	Inner spindle torque	**1,200 Nm**
Maximum spindle speed	**230 rpm**	Maximum carriage feed speed	**70 m/min**
Minimum entry angle	**0 °**	Maximum entry angle	**30 °**

DRILL RODS AND BORE

Drill pipe length	**3 m**	Onboard rod capacity	**132 m**
Rod count	**44 szt.**	Minimum bend radius	**35 m**
Pilot bore diameter	**140 mm**	Indicative maximum bore length	**200 m**

DRILLING FLUID SYSTEM

Mud pump flow rate	**190 l/min**	Mud pump pressure	**85 bar**

POWERTRAIN AND ENGINE

Powertrain type	**diesel**	Engine manufacturer	**Cummins**
Engine power	**115 kW**	Emission standard	**Stage V**
Fuel tank capacity	**134 l**		

DIMENSIONS AND WEIGHT

Weight	**12,760 kg**	Transport length	**7,020 mm**
Transport width	**1,910 mm**	Transport height	**2,782 mm**

EQUIPMENT AND CAPABILITIES

Dual-rod drilling system	**Yes**	Automatic rod exchange	**Yes**
Enclosed operator cabin	**Yes**	Maximum backreaming diameter	**355 mm**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.