

HDD DRILL

TRACTO GRUNDODRILL JCS300

TRACTO Manufacturer: **TRACTO** · Niemcy

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
300 kN	**13,000 Nm**

ENGINE POWER
231 kW

Technical specifications

PERFORMANCE			
Pullback force	**300 kN**	Thrust force	**300 kN**
Maximum spindle torque	**13,000 Nm**	Maximum spindle speed	**200 rpm**
Minimum entry angle	**0 °**	Maximum entry angle	**29 °**

DRILL RODS AND BORE			
Drill pipe length	**4.5 m**	Drill pipe diameter	**104 mm**
Onboard rod capacity	**315 m**	Minimum bend radius	**70 m**

DRILLING FLUID SYSTEM			
Mud pump flow rate	**750 l/min**	Mud pump pressure	**60 bar**

POWERTRAIN AND ENGINE			
Powertrain type	**diesel**	Engine power	**231 kW**
Fuel tank capacity	**295 l**		

DIMENSIONS AND WEIGHT

Weight	**23,600 kg**	Transport length	**8,630 mm**
Transport width	**2,550 mm**	Transport height	**2,980 mm**

EQUIPMENT AND CAPABILITIES

Automatic rod exchange	**Yes**	Enclosed operator cabin	**Yes**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.