

HDD DRILL

Ditch Witch JT28

Manufacturer: **Ditch Witch** · USA

PULLBACK FORCE	MAXIMUM SPINDLE TORQUE
124 kN	**5,690 Nm**

ENGINE POWER
97 kW

Technical specifications

PERFORMANCE

Pullback force	**124 kN**	Thrust force	**124 kN**
Maximum spindle torque	**5,690 Nm**	Maximum spindle speed	**220 rpm**
Maximum carriage feed speed	**55 m/min**	Minimum entry angle	**9 °**
Maximum entry angle	**20 °**		

DRILL RODS AND BORE

Drill pipe length	**3 m**	Drill pipe diameter	**60 mm**
Rod count	**55 szt.**	Minimum bend radius	**37.5 m**

DRILLING FLUID SYSTEM

Mud pump flow rate	**189 l/min**	Mud pump pressure	**83 bar**

POWERTRAIN AND ENGINE

Powertrain type	**diesel**	Engine manufacturer	**Cummins**
Engine power	**97 kW**	Emission standard	**EU Stage IV / EPA Tier 4**
Fuel tank capacity	**182 l**		

DIMENSIONS AND WEIGHT

Weight	**9,689 kg**	Transport length	**5,900 mm**
Transport width	**2,200 mm**	Transport height	**2,530 mm**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.