

PNEUMATIC PIERCING TOOL

TRACTO GRUNDOMAT P+ 145 SRV

TRACTO Manufacturer: **TRACTO** · Niemcy

TOOL DIAMETER	LENGTH
145 mm	**2,024 mm**
WEIGHT	AIR CONSUMPTION
168 kg	**3.4 m³/min**

Technical specifications

BASIC INFORMATION

Family	**GRUNDOMAT**	Model	**GRUNDOMAT P+ 145 SRV**
Version	**serwo**	Generation	**P+ (2026)**

DIMENSIONS AND WEIGHT

Tool diameter	**145 mm**	Length	**2,024 mm**
Weight	**168 kg**	Short version	**No**

PNEUMATIC SUPPLY

Working pressure	**7 bar**	Air consumption	**3.4 m³/min**

IMPACT MECHANISM

Impact rate – servo control	**320 1/min**

HEAD AND DESIGN

Head type	**koronowa lub stopniowana (konfiguracja)**	Head movement	**ruchoma**
Replaceable head	**Yes**		

CONTROL AND REVERSE

Reverse	**Yes**	Reverse system	**przełączanie dźwignią stacji sterowania**
Control system	**sterowanie serwo (SRV)**	Remote reverse	**Yes**

BORE PARAMETERS

Guided operation	**No**		

PIPE INSTALLATION

Maximum pipe diameter	**125 mm**	Pipe pulling	**Yes**
Supported pipe materials	**PE, PVC**		

APPLICATIONS

Primary application	**Przeciski pneumatyczne pod przyłącza i przeszkodami terenowymi**	Pipe installation	**Yes**

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.