

PNEUMATIC PIERCING TOOL

Hercu Pneumatic HP135 T3

Manufacturer: **Hercu Pneumatic** · Polska

TOOL DIAMETER

135 mm

Technical specifications

BASIC INFORMATION

Family	**HP**	Model	**HP135 T3**
Version	**standardowa**	Generation	**T3**

DIMENSIONS AND WEIGHT

Tool diameter	**135 mm**	Short version	**No**

HEAD AND DESIGN

Head type	**stała**	Head movement	**stała**
Replaceable head	**No**		

CONTROL AND REVERSE

Reverse	**Yes**	Reverse system	**zmiana kierunku przez pociągnięcie przewodu zasilającego (konfiguracja podstawowa)**
Remote reverse	**No**		

BORE PARAMETERS

Expander compatible	**No**	Guided operation	**No**

PIPE INSTALLATION

Maximum pipe diameter	**125 mm**	Pipe pulling	**Yes**
Simultaneous pipe installation	**No**	Back pulling	**No**
Supported pipe materials	**PE, PVC**		

APPLICATIONS

Primary application	**Pneumatyczne przeciski poziome w gruncie pod instalacje sieciowe**	Pipe installation	**Yes**
Steel pipe ramming	**No**	Pipe bursting and replacement	**No**
Pipe extraction	**No**	Pile driving	**No**

SOIL CONDITIONS

Cohesive soils	**No**	Non-cohesive soils	**No**
Compacted soils	**No**	Stony soils	**No**

LOCATING AND TRACKING

Sonde compatible	**No**		

The technical data is for information only and comes from the manufacturer's materials. Confirm the specifications with the manufacturer or distributor before buying or using the device.